



RED 10 AWG (TO CAB 25 AMP CIRCUIT BREAKER)

- NOTES:
1. UNLESS OTHERWISE INDICATED ALL WIRES ARE 16 AWG.
  2. UNLABELED AND Bxxx LABELED GROUND WIRES ARE BLACK 16 AWG UNLESS NOTED OTHERWISE.
  3. ALL WIRES LABELED Wxxx ARE WHITE 16 AWG.
  4. NUMBERED WIRES WITH A COMMON LETTER SUFFIX MAY BE DAISY CHAINED WITH ANY JOINTS AND CRIMPED ENDS SOLDERED.

SEE SHT 6 FOR SUPPLEMENTAL WIRING

<b>FRESNO ENGINEERING DESIGN GROUP</b> <small>5493 EAST OLIVE AVE. FRESNO CALIFORNIA 93727</small>		DESCRIPTION			ECO	DRN	DATE
		CAD FILE:	DRN:	DATE: 2/11/05	SCALE: NONE	SHT	5/6
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FRESNO ENGINEERING DESIGN GROUP. ANY REPRODUCTION IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF FRESNO ENGINEERING DESIGN IS PROHIBITED.</small>		<b>ELECTRICAL CIRCUIT-BASIC CHASSIS HARNESS</b>			MACHINE: XRM737, XRM742/842 DWG. NO. 25206-000		