



RED 10AWG (TO CAB 25 AMP CIRCUIT BREAKER)

- NOTES:
1. UNLESS OTHERWISE INDICATED ALL WIRES ARE 16 AWG. THOSE WITH AN ASTERISK PREFIX ARE 18 AWG (THESE MAY ALTERNATIVELY BE 16 AWG).
 2. BLK AND Bxxx LABELED GROUND WIRES ARE BLACK 16 AWG UNLESS NOTED OTHERWISE.
 3. ALL WIRES LABELED Wxxx ARE WHITE 16 AWG UNLESS NOTED OTHERWISE.
 4. NUMBERED WIRES WITH A COMMON LETTER SUFFIX MAY BE DAISY CHAINED WITH ANY JOINTS SOLDERED AFTER CRIMPING.

LAST REV 3: 5/9/05-MOVED W15A FROM 9-A TO 18-A ADD W77 & W78 PIGTAIL TO REMOTE 003 STEER VALVE
 SERVICE HARNESS:USE P/N 25013-000 CHASSIS HARNESS LDOM, 25017-000 OUTRIGGER HARNESS AND 25038-000 005 STEER HARNESS

FRESNO ENGINEERING DESIGN GROUP
 5493 EAST OLIVE AVE. FRESNO CALIFORNIA 93727

DESCRIPTION		ECD	DRN	DATE
CAD FILE:	DRN:	DATE: 9/16/04	SCALE: NONE	SHT 2/6
TITLE: OUTRIGGER MODEL ELECTRICAL CIRCUIT-CHASSIS		REV 3		
MACHINE: XRM1145/1245 & XRM1154/1254		DWG. NO. 25208-000		