

THE XTREME DIFFERENCE

At Xtreme Manufacturing, we build the largest range of heavy-duty and high-capacity telehandlers in North America, and we build them to outlast and outperform anything else in the industry—period.

- Long-life Boom Rollers**
Eliminates chatter for smoother boom operation
- 360° Visibility**
Operator view of entire work area through telehandler
- Boom Lift Point**
For safer handling of suspended loads
- Intuitive Controls**
One-armed boom & chassis sway
- Wider Outrigger Stance**
Safely handle loads at maximum extension

XR619-A

A CLASS CARRIAGE **COMPACT ROLLER BOOM**

19' MAX LIFT HEIGHT
11' FORWARD REACH
10,560lbs WEIGHT
12' 8" LENGTH (FORK FACE)
71" WIDTH
6' 6" HEIGHT
93" WHEELBASE

6,000lbs LIFT CAPACITY
74HP DEUTZ T4 FINAL

BOOM ANGLE: -2.3° - 69°
*6,000lbs. max. w/ fully retracted boom.

XR630-A

A CLASS CARRIAGE **COMPACT ROLLER BOOM**

30' 7" MAX LIFT HEIGHT
18' 5" FORWARD REACH
13,700lbs WEIGHT
16' 3" LENGTH (FORK FACE)
78" WIDTH
7" HEIGHT
116" WHEELBASE

6,000lbs LIFT CAPACITY
74HP DEUTZ T4 FINAL

BOOM ANGLE: 0° - 68°

XR843-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

43' MAX LIFT HEIGHT
26' 11" FORWARD REACH
25,500lbs WEIGHT
21' 3" LENGTH (FORK FACE)
101" WIDTH
8" HEIGHT
125" WHEELBASE

8,000lbs LIFT CAPACITY
74HP CUMMINS T4 FINAL
*optional 120hp

BOOM ANGLE: -7.8° - 70.5°

XR944-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

44' MAX LIFT HEIGHT
28' 10" FORWARD REACH
28,700lbs WEIGHT
21' 3" LENGTH (FORK FACE)
101" WIDTH
8" HEIGHT
125" WHEELBASE

9,000lbs LIFT CAPACITY
74HP CUMMINS T4 FINAL
*optional 120hp

BOOM ANGLE: -7.8° - 70.5°

XR1044-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

44' MAX LIFT HEIGHT
28' 10" FORWARD REACH
32,530lbs WEIGHT
21' 3" LENGTH (FORK FACE)
101" WIDTH
8" HEIGHT
125" WHEELBASE

10,000lbs LIFT CAPACITY
74HP CUMMINS T4 FINAL
*optional 120hp

BOOM ANGLE: -7.8° - 70.5°

XR1055-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

55' MAX LIFT HEIGHT
39' FORWARD REACH
34,600lbs WEIGHT
21' 4" LENGTH (FORK FACE)
101" WIDTH
8' 8" HEIGHT
125" WHEELBASE

10,000lbs LIFT CAPACITY
74HP CUMMINS T4 FINAL
*optional 120hp

BOOM ANGLE: -5.0° - 70°

XR1147-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

47' MAX LIFT HEIGHT
31' 6" FORWARD REACH
33,040lbs WEIGHT
21' 6" LENGTH (FORK FACE)
101" WIDTH
8' 1" HEIGHT
125" WHEELBASE

11,000lbs LIFT CAPACITY
74HP CUMMINS T4 FINAL
*optional 120hp

BOOM ANGLE: -8° - 70°

XR1247-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

47' MAX LIFT HEIGHT
31' 6" FORWARD REACH
37,200lbs WEIGHT
22' 2" LENGTH (FORK FACE)
101" WIDTH
8' 1" HEIGHT
125" WHEELBASE

12,000lbs LIFT CAPACITY
134HP CUMMINS T4 FINAL

BOOM ANGLE: -8° - 70°

XR1255-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

55' MAX LIFT HEIGHT
38' FORWARD REACH
40,220lbs WEIGHT
25' LENGTH (FORK FACE)
101" WIDTH
8' 2" HEIGHT
141" WHEELBASE

12,000lbs LIFT CAPACITY
134HP CUMMINS T4 FINAL

BOOM ANGLE: -5° - 68°

XR1285-B

B CLASS CARRIAGE **HIGH PIVOT ROLLER BOOM**

85' MAX LIFT HEIGHT
67' FORWARD REACH
63,500lbs WEIGHT
28' 8" LENGTH (FORK FACE)
102" WIDTH
10' 1" HEIGHT
151" WHEELBASE

12,000lbs LIFT CAPACITY
173HP CUMMINS T4 FINAL

BOOM ANGLE: -5° - 70°

XR1347-C

C CLASS CARRIAGE **HIGH CAPACITY ROLLER BOOM**

47' MAX LIFT HEIGHT
31' 6" FORWARD REACH
35,270lbs WEIGHT
22' 2" LENGTH (FORK FACE)
101" WIDTH
8' 2" HEIGHT
125" WHEELBASE

13,000lbs LIFT CAPACITY
134HP CUMMINS T4 FINAL

BOOM ANGLE: -8° - 70°

XR1547-C

C CLASS CARRIAGE **HIGH CAPACITY ROLLER BOOM**

47' MAX LIFT HEIGHT
32' 3" FORWARD REACH
38,090lbs WEIGHT
21' 3" LENGTH (FORK FACE)
101" WIDTH
8' 2" HEIGHT
125" WHEELBASE

15,000lbs LIFT CAPACITY
134HP CUMMINS T4 FINAL

BOOM ANGLE: -8° - 70°

CARRIAGES

FIXED CARRIAGE

Floating forks and adjustable side-to-side for efficient load entry and exit.

- Range from 48" to 96"

HYDRAULIC CARRIAGES

Fork Positioner Carriage
Swing Carriage
Side Shift Carriage
Side Tilt Carriage

- Range from 48" to 111"

PIPE & POLE GRAPPLE

Designed for handling multiple pipes or larger single pipe.

- Range from 72" to 96"
- Available with and without shoe

PERSONNEL PLATFORM

Now your telehandler can safely lift personnel.

- Range from 4'x4' to 8'x8'

TRUSS BOOM

Allows operator to set trusses and wall sections for wood and steel building construction.

- Range from 3' to 15'
- Available with and without shoe

For safe operation, consult your operator's manual and the applicable load chart for each attachment on your telehandler.

WARRANTY

10-5-2

10 YRS. OR 10,000 HRS. FRAME & CHASSIS WELEMENT

5 YRS. OR 5,000 HRS. BOOM WELEMENT & ROLLERS

2 YRS. OR 2,000 HRS. ENGINE, ELECTRICAL, TRANSMISSION, HYDRAULIC COMPONENTS & DRIVE AXLES

STANDARD FEATURES

- Long-life boom rollers
- 360° visibility
- Boom lift point
- Intuitive operator controls
- Standard auxiliary hydraulics
- Solid steel plate chassis
- Steel dash
- Ductile steel manifold
- Easy cab-mounted grab handles
- Reliable tier 4 compliant engines
- Master disconnect switch
- Axle-mounted outriggers
- Wider outrigger stance
- Large cross-section boom
- Easy tie-downs
- Heavy-duty pre-cleaner

- Additional HP hydraulic filter
- Direct engine/trans. connection
- Display screen
- Suspension seat
- Easy service access
- Protected tilt & extend cylinders
- Steel hydraulic & fuel tanks
- Long-life Lexan labels
- Heavy-duty boom chains
- Suspended pedals
- Electrical ring terminals
- Large-capacity fuel tanks
- Trunion-mounted sway cylinders
- Melonite pins
- Rear axle stabilization (RAS)
- Center-mounted power train